

X-LITE THERMOPLASTIC CASTING/SPLINTING MATERIAL

M A T E R I A L S A F E T Y D A T A S H E E T

EFFECTIVE DATE : _____

1. IDENTIFICATION

PRODUCT NAME : X-LITE
CHEMICAL NAME : X-LITE
CHEMICAL FAMILY : POLYCAPROLACTONE
MOLECULAR WEIGHT : 32.000
DEPARTMENT OF TRANSPORTATION : HAZARD CLASSIFICATION : NONE
SHIPPING NAME : NONE

2. PHYSICAL DATA

MELTING POINT : 68° à 72°C
DENSITY : 49 g/cm³
PER CENT VOLATILES BY VOLUME : /
APPEARANCE AND ODOR : WHITE, WITHOUT ODOR

3. INGREDIENTS

MATERIAL	%	TLV (Units)	HAZARD
CAPA 560	80%		
PURE COTON	20%		

4. FIRE AND EXPLOSION HAZARD DATA

AUTOIGNITION TEMPERATURE	260°C
EXTINGUISHING MEDIA	Use water spray, carbon dioxide, dry chemical, alcohol-type or universal-type foams applied by manufacturer's recommended technique
SPECIAL FIRE FIGHTING PROCEDURES	NONE
UNUSUAL FIRE AND EXPLOSION HAZARDS	NONE

TEL: +44 (0)151-448 1
FAX: +44 (0)151-448 1
website: <http://www.algeos.com>
email: algeopl@msn.com